

Zestawienie studzienek DN425mm zlewnia Witos

Pkt	Studnia średnica studni	Rt [m]	Hst [m]	D1 [mm]	RD1[°]	D2 [mm]	RD2 [m]	KD2 °	Dw1 [mm]	Rw1 [m]	Kw1 °	typ	Dw2 [mm]	Rw2 [m]	Kw2 °	typ
St1	Studzienka PE DN425	132,83	2,92	200,0	129,9	200,0	129,9	180	160,0	129,9	270					
St2	Studzienka PE DN425	132,88	2,93	200,0	130,0	200,0	130,0	208								
St3	Studzienka PE DN425	132,89	2,93	200,0	130,0	200,0	130,0	180	160,0	131,0	233	in situ				
St4	Studzienka PE DN425	132,93	2,93	200,0	130,0	200,0	130,0	156								
St5	Studzienka PE DN425	132,98	2,94	200,0	130,0	200,0	130,0	180	160,0	130,5	270	in situ				
St6	Studzienka PE DN425	133,14	2,96	200,0	130,2	200,0	130,2	169								
St7	Studzienka PE DN425	133,28	2,98	200,0	130,3	200,0	130,3	111								
St8	Studzienka PE DN425	133,43	3,00	200,0	130,4	200,0	130,4	180	160,0	131,5	270	in situ				
St9	Studzienka PE DN425	133,59	3,00	200,0	130,6	200,0	130,6	234								
St10	Studzienka PE DN425	133,21	1,96	200,0	131,3	200,0	131,3	180	160,0	131,3	90					
St11	Studzienka PE DN425	133,64	2,06	200,0	131,6	200,0	131,6	182	160,0	131,6	90					
St12	Studzienka PE DN425	133,83	3,16	200,0	130,7	200,0	130,7	180	160,0	131,7	90	in situ				
St13	Studzienka PE DN425	133,86	3,18	200,0	130,7	200,0	130,7	180	160,0	132,0	267	in situ				
St14	Studzienka PE DN425	133,94	3,22	200,0	130,7	200,0	130,7	180	160,0	131,8	109	in situ				
St15	Studzienka PE DN425	134,06	3,29	200,0	130,8	200,0	130,8	180	160,0	132,0	100	in situ				
St16	Studzienka PE DN425	134,14	3,32	200,0	130,8	200,0	130,8	182	160,0	132,1	270	in situ				
St17	Studzienka PE DN425	134,30	3,39	200,0	130,9	200,0	130,9	182	160,0	132,2	92	in situ				
St18	Studzienka PE DN425	134,34	3,42	200,0	130,9	200,0	130,9	180	160,0	132,2	256	in situ				
St19	Studzienka PE DN425	134,48	3,48	200,0	131,0	200,0	131,0	183								
St20	Studzienka PE DN425	136,30	3,45	200,0	132,9	200,0	132,9	180								
St21	Studzienka PE DN425	136,75	3,59	200,0	133,2	200,0	133,2	180	160,0	134,9	90	in situ				
St22	Studzienka PE DN425	136,79	3,52	200,0	133,3	200,0	133,3	180	160,0	133,8	270	in situ				
St23	Studzienka PE DN425	136,77	3,33	200,0	133,4	200,0	133,4	179	160,0	134,3	270	in situ	160,0	135,0	106	in situ
St24	Studzienka PE DN425	136,78	3,23	200,0	133,6	200,0	133,6	180	160,0	134,7	270	in situ	160,0	135,1	92	in situ
St25	Studzienka PE DN425	136,23	2,48	200,0	133,8	200,0	133,8	180	160,0	134,7	90	in situ				
St30	Studzienka PE DN425	134,70	3,48	200,0	131,2	200,0	131,2	181	160,0	132,6	270	in situ				
St31	Studzienka PE DN425	134,61	3,35	200,0	131,3	200,0	131,3	180	160,0	132,6	270	in situ				
St32	Studzienka PE DN425	134,56	3,27	200,0	131,3	200,0	131,3	180	160,0	132,5	90	in situ				
St33	Studzienka PE DN425	134,41	3,01	200,0	131,4	200,0	131,4	180	160,0	132,4	90	in situ				
St34	Studzienka PE DN425	134,31	2,65	200,0	131,7	200,0	131,7	180	160,0	132,2	262	in situ				
St35	Studzienka PE DN425	134,30	2,57	200,0	131,7	200,0	131,7	180	160,0	132,3	270	in situ				
St36	Studzienka PE DN425	134,30	2,56	200,0	131,7	200,0	131,7	180	160,0	132,2	90	in situ				
St37	Studzienka PE DN425	134,31	2,55	200,0	131,8	200,0	131,8	180	160,0	131,8	90					
St38	Studzienka PE DN425	134,33	2,47	200,0	131,9	200,0	131,9	180	160,0	132,4	265	in situ				
St39	Studzienka PE DN425	134,39	2,27	200,0	132,1	200,0	132,1	180	160,0	132,2	228		160,0	132,2	90	
St40	Studzienka PE DN425	134,38	2,16	200,0	132,2	200,0	132,2	180	160,0	132,3	90					
St41	Studzienka PE DN425	134,38	2,13	200,0	132,3	200,0	132,3	180	160,0	132,3	270					
St42	Studzienka PE DN425	134,39	2,05	200,0	132,3	200,0	132,3	180	160,0	132,4	93					
St43	Studzienka PE DN425	134,57	2,15	200,0	132,4	200,0	132,4	180	160,0	132,5	270					
St44	Studzienka PE DN425	134,85	2,27	200,0	132,6	200,0	132,6	180	160,0	133,1	270	in situ				
St45	Studzienka PE DN425	134,86	2,26	200,0	132,6	200,0	132,6	180	160,0	132,6	93					
St46	Studzienka PE DN425	134,95	2,26	200,0	132,7	200,0	132,7	180	160,0	132,7	91					
St47	Studzienka PE DN425	134,97	2,25	200,0	132,7	200,0	132,7	180	160,0	132,8	270					
St48	Studzienka PE DN425	135,08	2,30	200,0	132,8	200,0	132,8	180	160,0	132,8	90					
St49	Studzienka PE DN425	135,41	2,49	200,0	132,9	200,0	132,9	180	160,0	133,4	90	in situ				
St50	Studzienka PE DN425	135,39	2,41	200,0	133,0	200,0	133,0	181	160,0	133,5	90	in situ				
St51	Studzienka PE DN425	135,37	2,37	200,0	133,0	200,0	133,0	180	160,0	133,0	270					
St52	Studzienka PE DN425	135,33	2,30	200,0	133,0	200,0	133,0	180	160,0	133,1	92					
St53	Studzienka PE DN425	135,20	2,07	200,0	133,1	200,0	133,1	180	160,0	133,2	270					
St54	Studzienka PE DN425	135,34	2,18	200,0	133,2	200,0	133,2	180	160,0	133,2	90					
St55	Studzienka PE DN425	135,61	2,41	200,0	133,2	200,0	133,2	180	160,0	133,7	253	in situ				
St56	Studzienka PE DN425	136,62	3,27	200,0	133,4	200,0	133,4	180	160,0	134,2	270	in situ				
St57	Studzienka PE DN425	136,97	3,51	200,0	133,5	200,0	133,5	180	160,0	134,5	270	in situ				
St58	Studzienka PE DN425	137,08	3,58	200,0	133,5	200,0	133,5	180	160,0	135,2	90	in situ				
St59	Studzienka PE DN425	137,94	4,26	200,0	133,7	200,0	133,7	180	160,0	135,3	269	in situ	160,0	135,3	105	in situ
St60	Studzienka PE DN425	138,43	4,60	200,0	133,8	200,0	133,8	186								
St61	Studzienka PE DN425	138,35	4,34	200,0	134,0	200,0	134,0	180	160,0	136,4	251	in situ				
St62	Studzienka PE DN425	137,91	3,49	200,0	134,4	200,0	134,4	180	160,0	134,9	88	in situ				
St63	Studzienka PE DN425	138,16	3,63	200,0	134,5	200,0	134,5	180	160,0	135,5	90	in situ				
St64	Studzienka PE DN425	138,22	3,67	200,0	134,6	200,0	134,6	180	160,0	136,6	90	in situ				
St65	Studzienka PE DN425	137,70	2,87	200,0	134,8	200,0	134,8	159								
St66	Studzienka PE DN425	137,63	2,40	200,0	135,2	200,0	135,2	180	160,0	135,8	90	in situ				
St67	Studzienka PE DN425	137,63	2,37	200,0	135,3	200,0	135,3	180	160,0	135,9	90	in situ				
St68	Studzienka PE DN425	137,67	1,97	200,0	135,7	200,0	135,7	180	160,0	135,7	103					